

Programming Principles in Python (CSCI 503/490)

Dictionaries

Dr. David Koop

(some slides adapted from Dr. Reva Freedman)

Updating collections

- There are three ways to deal with operations that update collections:
 - Returns an **updated copy** of the collection
 - Updates the collection **in place**
 - Updates the collection in place **and returns it**
- `list.sort` and `list.reverse` work **in place** and **don't return** it
- `sorted` and `reversed` return an **updated copy**
 - `reversed` actually returns an iterator
 - these also work for immutable sequences like strings and tuples

Tuple Packing and Unpacking

- ```
def f(a, b):
 if a > 3:
 return a, b-a # tuple packing
 return a+b, b # tuple packing
```
- ```
c, d = f(4, 3) # tuple unpacking
```
- Make sure to unpack the correct number of variables!
- ```
c, d = a+b, a-b, 2*a # ValueError: too many values to unpack
```
- Sometimes, check return value before unpacking:
  - ```
retval = f(42)  
if retval is not None:  
    c, d = retval
```

Tuple Packing and Unpacking

- ```
def f(a, b):
 if a > 3:
 return a, b-a # tuple packing
 return a+b, b # tuple packing
```
- ```
c, d = f(4, 3) # tuple unpacking
```

```
t = (a, b-a)  
return t
```

- Make sure to unpack the correct number of variables!
- ```
c, d = a+b, a-b, 2*a # ValueError: too many values to unpack
```
- Sometimes, check return value before unpacking:
  - ```
retval = f(42)  
if retval is not None:  
    c, d = retval
```

Tuple Packing and Unpacking

- ```
def f(a, b):
 if a > 3:
 return a, b-a # tuple packing
 return a+b, b # tuple packing
```

```
t = (a, b-a)
return t
```

- ```
c, d = f(4, 3) # tuple unpacking
```

```
t = f(4, 3)  
(c, d) = t
```

- Make sure to unpack the correct number of variables!
- ```
c, d = a+b, a-b, 2*a # ValueError: too many values to unpack
```
- Sometimes, check return value before unpacking:
  - ```
retval = f(42)  
if retval is not None:  
    c, d = retval
```

Scope

- The **scope** of a variable refers to where in a program it can be referenced
- Python has three scopes:
 - **global**: defined outside a function
 - **local**: in a function, only valid in the function
 - **nonlocal**: can be used with nested functions
- Python allows variables in different scopes to have the **same name**

Global keyword

- ```
def f(): # no arguments
 x = 2
 print("x inside:", x)
```

```
x = 1
f()
print("x outside:", x)
```

- Output:
  - x inside: 2
  - x outside: 1

- ```
def f(): # no arguments
    global x
    x = 2
    print("x inside:", x)
```

```
x = 1
f()
print("x outside:", x)
```

- Output:
 - x inside: 2
 - x outside: 2

Is Python pass-by-value or pass-by-reference?

Pass by Value or Pass by Reference?

- ```
def change(inner_list):
 inner_list = [9,8,7]
```

```
outer_list = [0,1,2]
change_list(outer_list)
outer_list # [0,1,2]
```

- Looks like pass by value!

- ```
def change(inner_list):  
    inner_list.append(3)
```

```
outer_list = [0,1,2]  
change_list(outer_list)  
outer_list # [0,1,2,3]
```

- Looks like pass by reference!

Pass by object reference

- AKA passing object references by value
- Python doesn't allocate space for a variable, it just links identifier to a value
- **Mutability** of the object determines whether other references see the change
- Any immutable object will act like pass by value
- Any mutable object acts like pass by reference unless it is reassigned to a new value

Assignment 2

- Due Today
- Python control flow and functions
- Do not use containers like lists!
- Compute Compound Interest and Compare Situations
- Make sure to follow instructions
 - Name the submitted file a2.ipynb
 - Put your name and z-id in the first cell
 - Label each part of the assignment using markdown
 - Make sure to produce output according to specifications

Extra Credit Opportunity

- Participate in a research project on notebooks
- Will out send a link
- Shouldn't need much more than basic code knowledge
- Receive 20 points extra credit
- Takes ~1 hour
- Study is anonymous; just report the code you receive at the end

- If you cannot participate and would like an alternate extra credit activity, please let me know

Default Parameter Values

- ```
def rectangle_area(width=30, height=20):
 return width * height
```
- If no argument passed for parameter, it is set to the default value
- Don't use mutable values as defaults!
  - ```
def append_to(element, to=[]):  
    to.append(element)  
    return to
```
- Use None as a default instead:
 - ```
def append_to(element, to=None):
 if to is None:
 to = []
 to.append(element)
 return to
```

[Deitel & Deitel]

# Keyword Arguments

---

- Keyword arguments allow someone calling a function to specify exactly which values they wish to specify without specifying all the values
- This helps with long parameter lists where the caller wants to only change a few arguments from the defaults
- ```
def f(alpha=3, beta=4, gamma=1, delta=7, epsilon=8, zeta=2,  
      eta=0.3, theta=0.5, iota=0.24, kappa=0.134):  
    # ...
```
- ```
f(beta=12, iota=0.7)
```

# Positional & Keyword Arguments

---

- Generally, any argument can be passed as a keyword argument
- ```
def f(alpha, beta, gamma=1, delta=7, epsilon=8, zeta=2,  
      eta=0.3, theta=0.5, iota=0.24, kappa=0.134):  
    # ...
```
- `f(5, 6)`
- `f(alpha=7, beta=12, iota=0.7)`

Position-Only Arguments

- PEP 570 introduced position-only arguments
- Sometimes it makes sense that certain arguments must be position-only
- Certain functions (those implemented in C) only allow position-only: `pow`
- Add a slash (/) to delineate where keyword arguments start
- ```
def f(alpha, beta, /, gamma=1, delta=7, epsilon=8, zeta=2,
 eta=0.3, theta=0.5, iota=0.24, kappa=0.134):
 # ...
```

  - `f(alpha=7, beta=12, iota=0.7) # ERROR`
  - `f(7, 12, iota=0.7) # WORKS`

# Arbitrary Argument Containers

---

- `def f(*args, **kwargs):`  
    `# ...`
- `args`: a list of arguments
- `kwargs`: a key-value dictionary of arguments
- Stars in function signature, not in use
- Can have named arguments before these arbitrary containers
- Any values set by position will not be in `kwargs`:
- `def f(a, *args, **kwargs):`  
    `print(args)`  
    `print(kwargs)`  
    `f(a=3, b=5) # args is empty, kwargs has only b`

# Programming Principles: Defining Functions

---

- List arguments in an order that makes sense
  - May be convention  $\Rightarrow \text{pow}(x, y)$  means  $x^y$
  - May be in order of expected frequency used
- Use default parameters when meaningful defaults are known
- Use position-only arguments when there is no meaningful name or the syntax might change in the future

# Calling module functions

---

- Some functions exist in modules (we will discuss these more later)
- Import module
- Call functions by prepending the module name plus a dot
- `import math`  
`math.log10(100)`  
`math.sqrt(196)`

# Calling object methods

---

- Some functions are defined for objects like strings
- These are **instance methods**
- Call these using a similar dot-notation
- Can take arguments
- `s = 'Mary'`  
`s.upper()` # 'MARY'
- `t = ' extra spaces '`  
`t.strip()` # 'extra spaces'
- `u = '1+2+3+4'`  
`u.split(sep='+')` # ['1', '2', '3', '4']

# Dictionaries

# Dictionary

---

- AKA associative array or map
- Collection of key-value pairs
  - Keys are unique (repeats clobber existing)
  - Values need not be unique
- Syntax:
  - Curly brackets {} delineate start and end
  - Colons separate keys from values, commas separate pairs
  - `d = { 'DeKalb': 783, 'Kane': 134, 'Cook': 1274, 'Will': 546 }`
- No type constraints
  - `d = { 'abc': 25, 12: 'abc', ('Kane', 'IL'): 123.54 }`

# Dictionary Examples

| Keys              | Key type         | Values            | Value type                   |
|-------------------|------------------|-------------------|------------------------------|
| Country names     | <code>str</code> | Internet country  | <code>str</code>             |
| Decimal numbers   | <code>int</code> | Roman numerals    | <code>str</code>             |
| States            | <code>str</code> | Agricultural      | <code>list of str</code>     |
| Hospital patients | <code>str</code> | Vital signs       | <code>tuple of floats</code> |
| Baseball players  | <code>str</code> | Batting averages  | <code>float</code>           |
| Metric            | <code>str</code> | Abbreviations     | <code>str</code>             |
| Inventory codes   | <code>str</code> | Quantity in stock | <code>int</code>             |

[Deitel & Deitel]

# Collections

---

- A dictionary is **not** a sequence
- Sequences are **ordered**
- Conceptually, dictionaries need no order
- A dictionary is a **collection**
- Sequences are also collections
- All collections have length (`len`), membership (`in`), and iteration (loop over values)
- Length for dictionaries counts number of key-value **pairs**
  - Pass dictionary to the `len` function
  - `d = { 'abc': 25, 12: 'abc', ('Kane', 'IL'): 123.54 }`  
`len(d) # 3`

# Mutability

---

- Dictionaries are **mutable**, key-value pairs can be added, removed, updated
- (Each key must be immutable)
- Accessing elements parallels lists but with different "indices" possible
- Index → Key
- `d = { 'DeKalb': 783, 'Kane': 134, 'Cook': 1274, 'Will': 546 }`
- `d['Winnebago'] = 1023` # add a new key-value pair
- `d['Kane'] = 342` # update an existing key-value pair
- `d.pop('Will')` # remove an existing key-value pair
- `del d['Winnebago']` # remove an existing key-value pair

# Key Restrictions

---

- Many types can be keys... including tuples
  - `d = { 'abc': 25, 12: 'abc', ('Kane', 'IL'): 123.54 }`
- ...but the type must be immutable—lists cannot be keys
  - ~~`d = { ['Kane', 'IL']: 2348.35, [1, 2, 3]: "apple" }`~~
- Why?

# Key Restrictions

---

- Many types can be keys... including tuples
  - `d = { 'abc': 25, 12: 'abc', ('Kane', 'IL'): 123.54 }`
- ...but the type must be **immutable**\* —lists cannot be keys
  - ~~`d = { ['Kane', 'IL']: 2348.35, [1, 2, 3]: "apple" }`~~
- \*technically, the type must be hashable, but having a mutable and still hashable type almost always causes problems
- Why?
  - Dictionaries are fast in Python because are implemented as hash tables
  - No matter how long the key, python hashes it stores values by hash
  - Given a key to lookup, Python hashes it and finds the value quickly ( $O(1)$ )
  - If the key can mutate, the hash will not match the key!

# Principle

---

- Be careful using floats for keys
- Why?

# Principle

---

- Be careful using floats for keys

- `a = 0.123456`  
`b = 0.567890`

```
values = [a, b, (a / b) * b, (b / a) * a]
```

```
found = {}
```

```
for d in values:
```

```
 found[d] = True
```

```
len(found) # 3 !!!
```

```
found.keys() # [0.123456, 0.56789, 0.123455999999999999999998]
```

# Accessing Values by Key

---

- To get a value, we start with a key
- Things work as expected
  - `d['Kane'] + d['Cook']`
- If a value does not exist, get `KeyError`
  - `d['Boone'] > 12 # KeyError`

# Membership

---

- The membership operator (`in`) applies to **keys**
  - `'Boone' in d # False`
  - `'Cook' in d # True`
- To check the negation (if a key doesn't exist), use `not in`
  - `'Boone' not in d # True`
  - `not 'Boone' in d # True` (equivalent but less readable)
- Membership testing is much **faster** than for a list
- Checking and accessing at once
  - `d.get('Boone')` # no error, evaluates to `None`
  - `d.get('Boone', 0)` # no error, evaluates to `0` (default)

# Updating multiple key-value pairs

---

- Update adds or replaces key-value pairs
- Update from another dictionary:
  - `d.update({'Winnebago': 1023, 'Kane': 324})`
- Update from a list of key-value tuples
  - `d.update([('Winnebago', 1023), ('Kane', 324)])`
- Update from keyword arguments
  - `d.update(Winnebago=1023, Kane=324)`
  - Only works for strings!
- Syntax for update also works for constructing a **new** dictionary
  - `d = dict([('Winnebago', 1023), ('Kane', 324)])`
  - `d = dict(Winnebago=1023, Kane=324)`

# Dictionary Methods

| Method                                   | Meaning                                                                                        |
|------------------------------------------|------------------------------------------------------------------------------------------------|
| <code>&lt;dict&gt;.clear()</code>        | Remove all key-value pairs                                                                     |
| <code>&lt;dict&gt;.update(other)</code>  | Updates the dictionary with values from <code>other</code>                                     |
| <code>&lt;dict&gt;.pop(k, d=None)</code> | Removes the pair with key <code>k</code> and returns value or default <code>d</code> if no key |
| <code>&lt;dict&gt;.get(k, d=None)</code> | Returns the value for the key <code>k</code> or default <code>d</code> if no key               |
| <code>&lt;dict&gt;.items()</code>        | Returns iterable view over all pairs as (key, value) tuples                                    |
| <code>&lt;dict&gt;.keys()</code>         | Returns iterable view over all keys                                                            |
| <code>&lt;dict&gt;.values()</code>       | Returns iterable view over all values                                                          |

# Dictionary Methods

| Method                                   | Meaning                                                                                        | Mutate |
|------------------------------------------|------------------------------------------------------------------------------------------------|--------|
| <code>&lt;dict&gt;.clear()</code>        | Remove all key-value pairs                                                                     |        |
| <code>&lt;dict&gt;.update(other)</code>  | Updates the dictionary with values from <code>other</code>                                     |        |
| <code>&lt;dict&gt;.pop(k, d=None)</code> | Removes the pair with key <code>k</code> and returns value or default <code>d</code> if no key |        |
| <code>&lt;dict&gt;.get(k, d=None)</code> | Returns the value for the key <code>k</code> or default <code>d</code> if no key               |        |
| <code>&lt;dict&gt;.items()</code>        | Returns iterable view over all pairs as (key, value) tuples                                    |        |
| <code>&lt;dict&gt;.keys()</code>         | Returns iterable view over all keys                                                            |        |
| <code>&lt;dict&gt;.values()</code>       | Returns iterable view over all values                                                          |        |