Programming Principles in Python (CSCI 503/490)

Strings

Dr. David Koop

(some slides adapted from Dr. Reva Freedman)

List Comprehension

- ```
  output = []
  for d in range(5):
      output.append(d ** 2 - 1)
  ```

- Rewrite as a map:
  - `output = [d ** 2 - 1 for d in range(5)]`
- Can also filter:
  - `output = [d for d in range(5) if d % 2 == 1]`
- Combine map & filter:
  - `output = [d ** 2 - 1 for d in range(5) if d % 2 == 1]`
  ```

Comprehensions for other collections

- Dictionaries
  - `{k: v for (k, v) in other_dict.items() if k.startswith('a')}`
  - Example: one-to-one map inverses
    - `{v: k for (k, v) in other_dict.items()}`
    - Be careful that the dictionary is actually one-to-one!
- Sets:
  - `{s[0] for s in names}`
- Tuples? Not exactly
  - `(s[0] for s in names)`
  - Not a tuple, a **generator expression**

Iteration

- An **iterable** must be be able to return an iterator (defines `__iter__` method)
- An **iterator** must have two things:
  - a method to get the **next item** (defined `__next__` method)
  - a way to signal **no more** elements (raises `StopException`)
- You can call iteration methods directly, but rarely done
  - ```
    it = iter(my_list)
    first = next(it)
    ```
- `iter` asks for the iterator from the object
- `next` asks for the next element
- Usually just handled by loops, comprehensions, or generators
    ```

Generators

- Special functions that return **lazy** iterables
- Use less memory
- Change is that functions `yield` instead of `return`
- ```
  def square(it):
      for i in it:
          yield i*i
  ```
- If we are iterating through a generator, we hit the first yield and immediately return that first computation
- Generator expressions just shorthand (remember no tuple comprehensions)
  - `(i * i for i in [1,2,3,4,5])`
  ```

Efficient Evaluation

- Only compute when necessary, not beforehand
- ~~`u = compute_fast_function(s, t)`~~
  ~~`v = compute_slow_function(s, t)`~~

```
if s > t and s**2 + t**2 > 100:
    u = compute_fast_function(s, t)
    res = u / 100
else:
    v = compute_slow_function(s, t)
    res = v / 100
```

- slow function will not be executed unless the condition is true

Short-Circuit Evaluation

- Automatic, works left to right according to order of operations (and before or)
- Works for `and` and `or`
- and:
  - if **any** value is `False`, stop and return `False`
  -
```
a, b = 2, 3
a > 3 and b < 5
```
- or:
  - if **any** value is `True`, stop and return `True`
  -
```
a, b, c = 2, 3, 7
a > 3 or b < 5 or c > 8
```

Memoization

- Heavily used in functional languages because there is no assignment
- **Cache** (store) the results of a function call so that if called again, returns the result without having to compute
- If arguments of a function are **hashable**, fairly straightforward to do this for any Python function by caching in a dictionary
- In what contexts, might this be a bad idea?
  -
```
def memoize_random_int(a, b):
    if (a,b) not in random_cache:
        random_cache[(a,b)] = random.randint(a,b)
    return random_cache[(a,b)]
```
  - When we want to rerun, e.g. random number generators

CSAN Panel: Real Jobs in the Real World

- Tuesday, Oct. 7, 5:30–7:30pm
- Provides an insight into jobs from NIU alumni
- Food is Provided
- Sponsored by the Computer Science Alumni Network and the NIU Alumni Association

Assignment 4

- Upcoming, after Wednesday's exam

Test 1

- Wednesday, Oct. 1, 9:30-10:45am
- In-Class, paper/pen & pencil
- Covers material through last week
- Format:
  - Multiple Choice
  - Free Response
  - One extra 2-sided page for CSCI 503 Students
- Info on the course webpage

Functional Programming

- Programming without imperative statements like assignment
- In addition to comprehensions & iterators, have functions:
  - map: iterable of n values to an iterable of n transformed values
  - filter: iterable of n values to an iterable of m (m <= n) values
- Eliminates need for concrete looping constructs

Map

- Generator function (lazy evaluation)
- First argument is a **function**, second argument is the **iterable**
- ```
  def upper(s):
      return s.upper()
  ```
- `map(upper, ['sentence', 'fragment']) # generator`
- Similar comprehension:

```
- [upper(s) for s in ['sentence', 'fragment']] # comprehension
```

- This only calls `upper` **once**
- ```
  for word in map(upper, ['sentence', 'fragment']):
      if word == "SENTENCE":
          break
  ```

Filter

- Also a generator
- ```
  def is_even(x):
      return (x % 2) == 0
  ```
- `filter(is_even, range(10)) # generator`
- Similar comprehension:
  - `[d for d in range(10) if is_even(d)] # comprehension`
  ```

Lambda Functions

- `def is_even(x):`
  `    return (x % 2) == 0`
- `filter(is_even, range(10) # generator`
- Lots of code to write a simple check
- Lambda functions allow inline function definition
- Usually used for "one-liners": a simple data transform/expression
- `filter(lambda x: x % 2 == 0, range(10))`
- Parameters follow `lambda`, **no parentheses**
- **No** `return` keyword as this is implicit in the syntax
- JavaScript has similar functionality (arrow functions): `(d => d % 2 == 0)`

Strings

Strings

- Remember strings are sequences of characters
- Strings are collections so have `len`, `in`, and iteration
  - `s = "Huskies"`
    `len(s); "usk" in s; [c for c in s if c == 's']`
- Strings are sequences so have
  - indexing and slicing: `s[0], s[1:]`
  - concatenation and repetition: `s + " at NIU"; s * 2`
- Single or double quotes `'string1'`, `"string2"`
- Triple single-quotes or double-quotes: `"""A string over many lines"""`
- Escaped characters: `'\n'` (newline) `'\t'` (tab)

Unicode and ASCII

- Conceptual systems
- ASCII:
  - old 7-bit system (only 128 characters)
  - English-centric
- Unicode:
  - modern system
  - Can represent over 1 million characters from all languages + emoji 🎉
  - Characters have hexadecimal representation: é = U+00E9 and name (LATIN SMALL LETTER E WITH ACUTE)
  - Python allows you to type `"é"` or represent via code `"\u00e9"`

Unicode and ASCII

- Encoding: How things are actually stored
- ASCII "Extensions": how to represent characters for different languages
  - No universal extension for 256 characters (one byte), so…
  - ISO-8859-1, ISO-8859-2, CP-1252, etc.
- Unicode encoding:
  - UTF-8: used in Python and elsewhere (uses variable # of 1—4 bytes)
  - Also UTF-16 (2 or 4 bytes) and UTF-32 (4 bytes for everything)
  - Byte Order Mark (BOM) for files to indicate endianness (which byte first)

Codes

- Characters are still stored as bits and thus can be represented by numbers
  - `ord` → character to integer
  - `chr` → integer to character
  - `"\N{horse}"`: named emoji

Strings are Objects with Methods

- We can call methods on strings like we can with lists
  -
```
s = "Peter Piper picked a peck of pickled peppers"
s.count('p')
```
- Doesn't matter if we have a variable or a literal
  -
```
"Peter Piper picked a peck of pickled peppers".find("pick")
```

Finding & Counting Substrings

- `s.count(sub)`: Count the number of occurrences of `sub` in `s`
- `s.find(sub)`: Find the first position where `sub` occurs in `s`, else `-1`
- `s.rfind(sub)`: Like `find`, but returns the right-most position
- `s.index(sub)`: Like `find`, but raises a ValueError if not found
- `s.rindex(sub)`: Like `index`, but returns right-most position
- `sub in s`: Returns `True` if `s` contains `sub`
- `s.startswith(sub)`: Returns `True` if `s` starts with `sub`
- `s.endswith(sub)`: Returns `True` if `s` ends with `sub`

Removing Leading and Trailing Strings

- `s.strip()`: Copy of `s` with leading and trailing whitespace removed
- `s.lstrip()`: Copy of `s` with leading whitespace removed
- `s.rstrip()`: Copy of `s` with trailing whitespace removed
- `s.removeprefix(prefix)`: Copy of `s` with `prefix` removed (if it exists)
- `s.removesuffix(suffix)`: Copy of `s` with `suffix` removed (if it exists)

Transforming Text

- `s.replace(oldsub, newsub)`:
  Copy of `s` with occurrences of `oldsub` in `s` with `newsub`
- `s.upper()`: Copy of `s` with all uppercase characters
- `s.lower()`: Copy of `s` with all lowercase characters
- `s.capitalize()`: Copy of `s` with first character capitalized
- `s.title()`: Copy of `s` with first character of each word capitalized

Checking String Composition

String Method	Description
`isalnum()`	Returns True if the string contains only alphanumeric characters (i.e., digits & letters).
`isalpha()`	Returns True if the string contains only alphabetic characters (i.e., letters).
`isdecimal()`	Returns True if the string contains only decimal integer characters
`isdigit()`	Returns True if the string contains only digits (e.g., '0', '1', '2').
`isidentifier()`	Returns True if the string represents a valid identifier.
`islower()`	Returns True if all alphabetic characters in the string are lowercase characters
`isnumeric()`	Returns True if the characters in the string represent a numeric value w/o a + or - or .
`isspace()`	Returns True if the string contains only whitespace characters.
`istitle()`	Returns True if the first character of each word is the only uppercase character in it.
`isupper()`	Returns True if all alphabetic characters in the string are uppercase characters

[Deitel & Deitel]

Splitting

- `s = "Venkata, Ranjit, Pankaj, Ali, Karthika"`
- `names = s.split(',') # names is a list`
- `names = s.split(',', 3) # split by commas, split <= 3 times`
- separator may be multiple characters
- if no separator is supplied (`sep=None`), runs of consecutive whitespace delimit elements
- `rsplit` works in reverse, from the right of the string
- `partition` and `rpartition` for a single split with before, sep, and after
- `splitlines` splits at line boundaries, optional parameter to keep endings

Joining

- `join` is a method on the **separator** used to join a list of strings
- `','.join(names)`
  - `names` is a list of strings, `','` is the separator used to join them
- Example:
  - ```
    def orbit(n):
        # …
        return orbit_as_list
    print(','.join(orbit_as_list))
    ```
    ```

Formatting

- `s.ljust`, `s.rjust`: justify strings by adding fill characters to obtain a string with specified width
- `s.zfill`: `ljust` with zeroes
- `s.format`: templating function
  - Replace fields indicated by curly braces with corresponding values
  - `"My name is {} {}".format(first_name, last_name)`
  - `"My name is {1} {0}".format(last_name, first_name)`
  -
```
"My name is {first_name} {last_name}.format(
                        first_name=name[0], last_name=name[1])
```
  - Braces can contain number or name of keyword argument
  - Whole format mini-language to control formatting

Format Strings

- Formatted string literals (f-strings) prefix the starting delimiter with `f`
- Reference variables **directly**!
  - `f"My name is {first_name} {last_name}"`
- Can include expressions, too:
  - `f"My name is {name[0].capitalize()} {name[1].capitalize()}"`
- Same format mini-language is available

Format Mini-Language Presentation Types

- Not usually required for obvious types
- `:d` for integers
- `:c` for characters
- `:s` for strings
- `:e` or `:f` for floating point
  - `e`: scientific notation (all but one digit after decimal point)
  - `f`: fixed-point notation (decimal number)

Field Widths and Alignments

- After : but before presentation type
  - `f'[{27:10d}]' # '[        27]'`
  - `f'[{"hello":10}]' # '[hello     ]'`
- Shift alignment using < or >:
  - `f'[{"hello":>15}]' # '[          hello]'`
- Center align using ^:
  - `f'[{"hello":^7}]' # '[ hello ]'`

Numeric Formatting

- Add positive sign:
  - `f'[{27:+10d}]' # '[       +27]'`
- Add space but only show negative numbers:
  - `print(f'{27: d}\n{-27: d}') # note the space in front of 27`
- Separators:
  - `f'{12345678:,d}' # '12,345,678'`